

# FAW 50KVA

50kVA Prime / 55kVA Standby

Comprehensive Specification Sheet  
Electrical and Mechanical Data



**FAW**

3ph

# FAW 50KVA

50kVA Prime / 55kVA Standby / Three Phase

## FEATURES & BENEFITS

- 55kVA standby power at 230/400v @ 50Hz 1500rpm
- High-quality and reliable four-cylinder 3.86l turbocharged FAWDE diesel engine
- Ideal for home and business applications
- Silent canopy which can stand outside with lockable doors
- Automatic changeover (ATS), maintenance free batteries and trickle charger included
- H-specification insulation, brushless alternator with AVR provides stable output
- High-temperature and oil pressure sensor to protect against engine damage
- Easy to use digital controller with auto/manual start options
- All sets undergo a comprehensive testing/pre-delivery inspection prior to delivery
- Peace of mind of earlier of one year/1000 hour warranty



## CANOPY

- Ventilation parts are designed with modular principles
- Weather resistant and lined with sound reducing foam
- All metal canopy parts are painted with powder paint
- Panel window
- Lockable doors on each side
- Easy maintenance and operation
- Easy lifting and moving
- Thermally insulated engine exhaust system
- Exterior emergency stop push button
- Sound attenuated

## CHASSIS

- The complete generator set is mounted as a whole on a heavy duty fabricated, steel base frame
- Steel chassis and anti-vibration pads
- Base frame design incorporates an integral fuel tank
- The generator can be lifted or carefully pushed/pulled by the base frame
- Dial type fuel gauge on the fuel tank

## CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:

### AUTO MAINS FAILURE CONTROL PANEL

- Controller with Smartgen automatic transfer switch
- Smartgen HGM420N electronic controller
- Emergency stop push button
- Static battery charger
- Four-pole electrically and mechanically interlocked ATS

### GENERATING SET CONTROL MODULE SMARTGEN HGM420N FEATURES

- This module is used to monitor a mains supply and automatically start a standby generating set
- Shutdown alarms
- STOP/RESET-MANUAL-AUTO-TEST-START

### METERING VIA LCD DISPLAY

- Mains volts (L-L/L-N)
- Generator amps (L1, L2, L3)
- Generator frequency; generator (cos)
- Engine hours run; plant battery (volts)
- Engine oil pressure (psi and bar)

## Overview

|                    |        |
|--------------------|--------|
| Standby power      | 55kVA  |
| Prime power        | 50kVA  |
| Phase              | Three  |
| Dry weight         | 1076kg |
| Length             | 2250mm |
| Width              | 950mm  |
| Height             | 1200mm |
| Fuel tank capacity | 230l   |

- Engine speed (rpm)
- Engine temperature (degrees C)

### AUTOMATIC SHUTDOWN AND FAULT CONDITIONS

- Under/over speed; fail to start
- High engine temperature; fail to stop
- Low oil pressure; charge fail
- Under/over generator volts
- Under/over generator frequency
- Emergency stop/start failure
- Under/over mains voltage
- Charge failure

# FAW 50KVA

50kVA Prime / 55kVA Standby / Three Phase

## TECHNICAL SPECIFICATIONS

\*All ratings are quoted at maximum ratings at sea level and derating will be applicable for altitude and power factor.

### Engine

|                                 |  |
|---------------------------------|--|
| Engine make                     | FAW/FAWDE  |
| Engine model                    | 4DX22-65D  |
| Displacement                    | 3.86L  |
| Cylinder bore/Stroke            | 102mm x 118mm  |
| Fuel system                     | In-line fuel injection pump                                  |
| Governor                        | Electrical   |
| Cylinders                       | Four cylinders<br>water cooled                               |
| Engine output power (1500rpm)   | 48kW   |
| Turbocharged/normally aspirated | Turbocharged   |
| Cycle                           | Four stroke  |
| Combustion system               | Direct injection   |
| Compression ratio               | 17:1   |
| Fuel tank capacity              | 230L   |
| Fuel consumption 100%           | 12.9 l/h   |
| Fuel consumption 75%            | 9.7 l/h  |
| Fuel consumption 50%            | 6.5 l/h  |
| Fuel consumption 25%            | 3.2 l/h  |
| Oil type                        | 15W40  |
| Engine oil capacity             | 13L  |
| Cooling method                  | Water-cooled radiator/fan                                    |
| Coolant capacity                | 4.76L  |
| Starter                         | 24v DC<br>charge alternator                                  |
| Engine speed                    | 1500rpm  |
| Filters                         | Replaceable fuel filter/oil<br>filter/dry element air filter |
| Battery                         | Maintenance-free battery<br>including rack and cables        |
| Silencer                        | Exhaust silencer   |

### Alternator

|                         |  |
|-------------------------|--|
| Alternator make         | StromerPower                                 |
| Standby power output    | 55kVA  |
| Prime power output      | 50kVA  |
| Insulation class        | Class-H with circuit breaker<br>protection   |
| Type                    | Brushless                                    |
| Phase and connection    | Three phase/four wire                        |
| AVR                     | Included                                     |
| AVR model               | SX460  |
| Voltage regulation      | ± 1%   |
| Voltage                 | 230/400v                                     |
| Rated frequency         | 50Hz   |
| Voltage regulate change | ≤ ±10% UN                                    |
| Phase change rate       | ± 1%   |
| Power factor            | 0.8φ   |
| Protection class        | IP23 standard/screen<br>protected/drip-proof |
| Stator                  | 2/3 pitch                                    |
| Rotor                   | Single bearing                               |
| Excitation              | Self-exciting                                |
| Regulation              | Self-regulating                              |

### General

|  |                                       |
|--|---------------------------------------|
| Structure type                         | Silent weather resistant<br>enclosure |
| Dimensions<br>Length x Width x Height  | 2250mm x 950mm<br>x 1200mm            |
| Dry weight                             | 1076kg                                |
| ATS unit included                      | Included                              |
| Four-way protection<br>system included | Included                              |