



4HT4.3-G23

◎ Power

Engine Speed r/min	Type of Operation	Engine Power	Generator Power	
		kW	kW	kVA
1500	Prime Power	78	64	80
	Standby Power	86	70	88
1800	Prime Power	86	70	88
	Standby Power	95	75	93.5

- The engine performance is as per GB/T2820

- Ratings are based on GB/T1147.1.

→**Prime Power** : --- There is no time limit in the case of variable load operation. In any 250hours of continuous operation period, the variable load of average work load less than 70%of the prime power. The operation time in the situation of 100%prime power no more than 500 hours. Permit 10%overload running1hours in any 12 hours of continuous operation period. The overload 10% power running time of every year no more than 25 hours..

→**Standby Power**: The annual total standby power load should be less than 80%and the average running time shall be less than200 hours. Among them the standby power point should be no more than 25 hours a year.。

◎ SPECIFICATIONS

○ Engine Model	4HT4.3-G23
○ Engine Type	In-line,4 strokes,4 valves, water-cooled , Turbo charged
○ Combustion type	Direct injection
○ Cylinder Type	Dry liner
○ Number of cylinders	4
○ Bore × stroke	105× 124mm
○ Displacement	4.3 L
○ Compression ratio	17.3 : 1
○ Firing order	1-3-4-2
○ Injection timing	10°BTDC
○ Dry weight	450kg

◎ FUEL CONSUMPTION

○ Power

	L/h (1500r/min)	L/h (1800r/min)
25%	5.5	6.1
50%	9.9	11.2
75%	14.3	16.4
100%	19.5	21.6
110%	21.8	24.0

◎ FUEL SYSTEM

○ Injection pump	in-line “AD” type
○ Governor	Electronic regulator

○ Dimension (L×W×H)	1099×716×1078 mm
○ Rotation	CCW viewed from flywheel
○ Fly wheel housing	SAE NO.3
○ Fly wheel	SAE NO.11.5(tooth number of gear:127)

◎ MECHANISM

○ Type	Over head valve
○ Number of valve	Intake 2, exhaust 2 per cylinder
○ Valve lashes at cold	Intake 0.25mm Exhaust 0.50mm

◎ VALVE TIMING

	Opening	Close
○ Intake valve	20.9° BTDC	44.9° ABDC
○ Exhaust valve	51.7° BBDC	11.7° ATDC

◎ COOLING SYSTEM

○ Cooling method	Fresh water forced circulation
○ Water capacity (engine only)	6.8 liters
○ Lid Min. pressure	70kPa
○ Water pump	Centrifugal type driven by belt
○ Water pump Capacity	155L/min (1500r/min) 186L/min (1800r/min)
○ The maximum temp. of coolant in prime/ Standby power	104/100

○ Feed pump	Mechanical type
○ Injection nozzle	Multi hole type
○ Opening pressure	250 kg/cm ²
○ Fuel filter	Full flow, cartridge type
○ Used fuel	Diesel fuel oil

◎ LUBRICATION SYSTEM

○ Lub. Method	Fully forced pressure feed type
○ Oil pump	Gear type driven by crankshaft
○ Oil filter	Full flow, cartridge type
○ Oil pan capacity	High level 13 liters Low level 11 liters
○ Angularity limit	Front down 25 deg. Front up 35 deg. Side to side 35 deg.
○ Lub. Oil	Refer to Operation Manual

◎ ENGINEERING DATA

○ Heat rejection to coolant	9.3kcal/sec (1500r/min) 10.2kcal/sec (1800r/min)
○ Air flow	5.6m ³ /min (1500r/min) 7.2m ³ /min (1800r/min)
○ Exhaust gas flow	13.2m ³ /min (1500r/min) 17.0m ³ /min (1800r/min)
○ Exhaust gas temp.	600 °C
○ Max. permissible restrictions	3 kPa initial

- Thermostat
 - Wax-pellet type
 - Opening temp. 82°C
 - Full open temp. 95°C
- Cooling fan
 - Blower type, plastic
 - 500 mm diameter, 7 blades
 - Power consumption 3kw

- Intake system
 - 6 kPa final (need charge filter element)
- Exhaust system
 - 8 kPa max.

◎ **ELECTRICAL SYSTEM**

- Charging generator
 - 14V×80A
- Voltage regulator
 - Built-in type IC regulator
- Starting motor
 - 12V×4.2kW
- Battery Voltage
 - 12V
- Battery Capacity
 - 120 AH

